

PRODUCT INFORMATION

SC 258 E2

Combi tool and handy all-rounder – cutting and spreading with a single tool, higher cutting class, lighter weighing and better balance.



FACTS

- Successor model SC 258 E 2 will be replacing the SC 250 E2 with immediate effect.
- The rubber hand guard has been replaced by the multipart lever cover.
- The new slimmer D-handle is standing for more effective handling and an even better balance.
- The cutting class with round material per Euronorm could be elevated from „F“ to „G“.
- Weighing only 14.9kg without battery, the SC 258 E2 will be positioned below the important 15kg limit.

SC 258 E2

Cutting force up to	63,000 lbf./280 kN
Round steel up to ø ¹⁾	1.02 in./26 mm
Spreading force up to	157,000 lbf./700 kN
Spreading force 25 mm from tips end	7200 lbf./32 kN
Spreading distance	12.6 in./321 mm
Pulling force up to	7640 lbf./34 kN
Pulling distance	13 in./330 mm
Dimensions ²⁾	34.4 × 8.5 × 11.1 in./874 × 215 × 281 mm
Weight ³⁾	32.6 lbs./14.9 kg
NFPA classes	A6/B6/C6/D7/E7
EN cutting class	G
EN cutting performance	1G – 2F – 3F – 4F – 5G
Protection class	IP 54

¹⁾ according to EN 13204; NFPA 1936 ²⁾ l x w x h ³⁾ closed; w/o battery